
Product discontinued!
Replacement requirement only on request.
Replaced by series RFD.



NOVOHALL Angle Sensor touchless technology transmissive

Series RFA4000 analog





Special features

- touchless technology, magnetic measurement
- enables for transmissive measurements
- electrical range up to 360°
- simple mounting
- lateral magnet offset up to ±3 mm
- protection class IP67 / IP69k
- single and redundant versions
- unlimited mechanical lifetime
- resolution 12 bit
- independent linearity ±0.5 %
- very favourable price/performance ratio
- extremely flat design 30x30x7mm³

The sensor utilizes the orientation of a magnetic field for the determination of the measurement angle. Therefore, a magnet is attached to the rotating shaft. The magnetic field orientation is captured with an integrated circuit. An analogue output signal represents the calculated angle.

The extreme miniaturization of the sensor enables the application also in very small installation spaces. The housing is made of high grade temperature-resistant plastic material. The sensor is totally sealed and therefore is not sensitive to dust, dirt or moisture.


The two-part design of the sensor Series RFA and its position marker offers the customer maximal variability when mounting the sensor. The absence of shaft and bearing makes the assembly insensitive for customer application tolerances.

Measurements can be made transmissively through various (non-magnetic) materials.


Electrical connection is made via lead wires.

| Description | |
|------------------------|--|
| Housing | high grade, temperature resistant plastic |
| Electrical connections | lead wires AWG 20 (0.5 mm²) alternative soldering pins for PCB mounting |

Dimensions single version (Code 6 _ _)




Dimensions multi-channel version (Code 7 / 8 _ _)




| single Code 6 | | |
|--------------------|-------------------------|-------------------------|
| | partly redundant Code 7 | fully redundant Code 8 |
| Supply voltage +Ub | Supply voltage +Ub | Supply voltage +Ub 1 |
| GND | GND | GND 1 |
| Output | Output 1 | Output 1 |
| - | - | Supply voltage +Ub 2 |
| - | - | GND 2 |
| - | Output 2 | Output 2 |
| | GND Output - | GND GND Output Output 1 |


Output characteristic single (Code 6 _ _)





Output characteristics redundant (Code 7 / 8 _ _)



Position marker examples







Technical Data and further position markers see separate data sheet. Only Novotechnik approved magnets may be used.


| Type designations | RFA-4001 | | |
|---|---|-------------------|--|
| Mechanical Data | | | |
| Dimensions | see dimension drawing | | |
| Mounting | with 4 M4 screws (not included) | | |
| Mechanical travel | 360 continuous | ۰ | |
| Maximum operational speed | unlimited | min ⁻¹ | |
| Weight | ca. 10 | g | |
| Electrical Data | | | |
| Supply voltage Ub | 5 ±0.5 | VDC | |
| No-load supply current | typ. 15 (typ. 8 on request) per channel | | |
| Reverse voltage | yes, only supply lines | | |
| Short circuit protection, vs. GND and +Ub | yes | | |
| Measuring range | 0 30 up to 0 360, in 10° steps | | |
| Number of channels | 1/2 | | |
| Update rate | 5000 typ. | | |
| Resolution | 12 bit | | |
| Repeatability | 0.1 | 0 | |
| Independent linearity | ≤ 0.5 of signal range | % | |
| Output signal | ratiometric to Ub 0.25 V 4.75 V 0.5 4.5 V (load $\ge 1 \ k\Omega$) | | |
| TC at stroke angle 30 up to 170° TC at stroke angle 180 up to 360° | typical 100 typical 50 | ppm/K ppm/K | |
| nsulation resistance (500 VDC) | ≥ 10 | MΩ | |
| Cross-section lead wires | 0.5 | mm ² | |
| Environmental Data | | | |
| Temperature range | -40+125 | °C | |
| Vibration (IEC 60068-2-6) | 52000 | Hz | |
| , | $A_{\text{max}} = 0.75$ | mm | |
| | a _{max} = 20 | g | |
| Shock (IEC 60068-2-27) | 100 (6 ms) | | |
| Life | mechanical unlimited | | |
| MTTF (DIN EN ISO 13849-1 parts count method, w/o load) | 424 (single) | years | |
| | 464 (per channel) partly redundant 468 (per channel) fully redundant | years years | |
| Functional Safety | When using our products in safety-related systems, please contact us | | |
| Protection class (DIN EN 60529) | IP67 / IP69k | | |
| EMC compatibility | ISO 11452-2 Interference test in Absorber chamber ISO 11452-5 Interference test Stripline CISPR 25 Emitted interference CISPR 25 Conducted emission ISO 7637-1 Transients ISO 10506 ESD components check ISO 10605 ESD Handling & Packaging | | |
| Working distance A / magnet constant | Z-RFC-P03: A = 2 ±1 mm / magnet constant = 1.85 [°/mm²] Z-RFC-P04: A = 4.5 ±1.7 mm / magnet constant = 0.8 [°/mm²] | | |
| Lateral magnet offset (will cause additional linearity error) | max. ±3 mm (Z-RFC-P04), max. ±1.5 mm (Z-RFC-P03) The maximum error which is caused by lateral offset between sensor and position marker may be approximated as follows: | | |
| | Error $[^{\circ}]$ = magnet constant x (offset [mm]) ² The magnet constant depends from the position marker. | | |
| | Example: Z-RFC-P04: magnet constant = 0.8 °/mm ² ; offset = 0,5 mm Error [°] = 0.8 °/mm ² × $(0.5 \text{ mm})^2$ = 0.2 ° | | |

Novotechnik Messwertaufnehmer OHG

Postfach 4220 73745 Ostfildern (Ruit) Horbstraße 12 73760 Ostfildern (Ruit)

Telefon +49 711 44 89-0 Telefax +49 711 44 89-118 info@novotechnik.de www.novotechnik.de

© 01/2014 Subject to changes Printed in Germany



Required accessories

Position marker Z-RFC-P03, Art.No. 005658; Position marker Z-RFC-P04, Art.No. 005659; Position marker Z-RFC-P23, Art.No. 056074 (further position markers see separate data sheet Positionmarker_rotary)

Recommended accessories

Process-controlled indicators MAP... with display.

Available on request

Cable versions
Customized connectors
Specific angle ranges /
characteristics
SPI or PWM interface
Other interfaces