NOVOTURN Multi-turn Sensor Non-contacting

RSM-2800

Voltage







Special Features

- Non-contacting, magnetic
- Long life
- Measuring range 720° up to 5760° in 360°-steps (2 to 16 turns)
- True-Power-On system: counts turns even when not powered. Patented non-volatile technology does not require gears or batteries
- Available with push-on coupling or marked shaft
- Easy mounting
- Protection class IP54 up to IP67
- One or multi-channel versions
- Resolution 16 bits
- \bullet Linearity up to ±0,03 %
- Other configurations see separate data sheets



Applications

- Mechanical engineering
- Mobile machinery
- Driveline or steering systems
- Wire-actuated encoders
- Gate drives
- Motor sports

Multi-turn sensors that use the GMR technology (giant magneto resistance), provide absolute position values, do not require any reference signals and need no power supply or buffer battery for detecting the revolutions. The fact that rotations are detected even unpowered and the sensor does not lose its position information during a power failure, makes the RSM-2800 with its diameter of only 28 mm an extremely compact real True-Power-On rotary sensor.


The sensor operates magnetically and thus contactless allowing an extremely long life.

The sensor is able to detect angular positions over 2 to 16 revolutions with a high resolution of 16 bits.

Material	Housing: high grade, temperature resistant plastic PPS-GF40/SF50			
	Shaft: stainless steel, X8CrNiS18-9 1.4305			
Mounting	With 2 screws M4 and washers			
Fastening torque of mounting	max. 180 Nem			
Bearing	Sintered bronze bushing			
Electrical connection	Cable 4x 0.5 mm² (AWG 20), TPE, shielded / Connector M12x1, A-coded with cable L = 0.15 m			
Mechanical Data	See dimension drawing			
Dimensions	See dimension drawing			
Dimensions Mechanical travel	See dimension drawing 360° continuous 20 N (axial / radial)			
Dimensions Mechanical travel Permitted shaft load	360° continuous			
	360° continuous			




Ordering Specifications





Drawing



CAD data see www.novotechnik.de/en/download/caddata/



When the marking of the shaft is pointing towards the electrical outlet, the sensor output is located on an integer turn position.



Technical Data

Туре	RSM-2811			
Output signal	0.1 10 V			
Load	≥ 10 kΩ			
Number of channels	1/2			
Start-up time	typ. 10 ms			
Response time	max. 2 ms			
Measuring range	0 720° up to 0 5760° in 360°-steps			
Independent linearity	2 turns: typ. ≤ ±0.25 %FS, max. ≤ ±0.35 %FS			
	3 turns: typ. ≤ ±0.167 %FS, max. ≤ ±0.267 %FS			
	6 turns: typ. ≤ ±0.083 %FS, max. ≤ ±0.183 %FS			
	10 turns: typ. ≤ ±0.05 %FS, max. ≤ ±0.15 %FS			
	16 turns: typ. ≤ ±0.031 %FS, max. ≤ ±0.131 %FS			
Resolution	16 bits			
Repeatability	≤±0.5°			
Hysteresis	≤±1°			
Temperature error	±0.31 %FS			
Supply voltage Ub	24 VDC (18 30 VDC)			
Current consumption w/o load	typ. 30 mA			
Polarity protection	yes (supply lines and outputs)			
Short circuit protection	yes (vs. GND and supply voltage Ub)			
Insulation resistance (500 VDC)	≥ 10 MΩ			
Environmental Data				
Max. operational speed	800 rpm			
Vibration IEC 60068-2-6	20 g, 5 2000 Hz, Amax = 0.75 mm			
Shock IEC 60068-2-27	50 g, 6 ms			
Protection class DIN EN 60529	IP54 / IP65 / IP67			
Operating temperature	-40 +85°C			
	-25 +85°C (connector M12)			
Insensitivity to magnetic DC fields	< 15 mT			
Life	> 50 Mio. movements (mechanically)			
MTTF (IEC 60050)	184 years (per channel)			
EMC Compatibility				
EN 61000-4-2 ESD (contact/air discharge)	4 kV, 8 kV			
EN 61000-4-3 Electromagnetic fields (RFI)	10 V/m			
EN 61000-4-4 Fast transients (burst)	1 kV			
EN 61000-4-6 Cond. disturbances (HF field				
EN 61000-4-8 Magnetic fields	30 A/m			
EN 55011 Noise radiation	Class B			


Connection Assignment

Signal	Cable	Connector	Cable	Connector
	code 2	code 5	code 2	code 5
	One-channel	One-channel	Two-channel	Two-channel
Supply voltage Ub	GN	Pin 1	GN	Pin 1
GND	BN	Pin 3	BN	Pin 3
Signal output 1	WH	Pin 2	WH	Pin 2
Signal output 2	-	-	YE	Pin 4
Do not connect / not assigned	YE	Pin 4	-	-
	Connect cable shielding to GND			






Technical Data Output Characteristics






Sensor Mounting



7-105-G-6



Connector System M12





Protection class IP67 DIN EN 60529





Very good Electromagnetic Compatibiliy (EMC) and shield systems

Very good resistance to oils, coolants and lubricants






Page 7



Signal Processing





Connecting Options on request



M12 connector

- Customized lengths
- 3-, 4-, 6- and 8-pole versions
- Protection class IP68 Ordering codes of standard versions see ordering specifications



Molex Mini Fit jr.

- Customized length and lead wires
- 3-, 4- and 6-pole versions
 On request

- Tyco AMP Super Seal
 - Pin- and bushing housing Customized lengths
 - 3-, 4- and 6-pole versions
 - Protection class IP67
 - On request



- Molex Mini Fit jr. Customized length and lead wires 3-, 4- and 6-pole versions
- On request



Deutsch DTM 04

- Pin- and bushing housing
 Customized lengths
 3-, 4- and 6-pole versions
- Protection class IP67
- On request



Page 9

- ITT Cannon Sure Seal connector
- Customized lengths
- 3-, 4- and 6-pole versions Protection class IP67
- On request



Novotechnik Messwertaufnehmer OHG P.O.Box 4220 73745 Ostfildern (Germany) Horbstrasse 12 73760 Ostfildern (Germany) Phone +49 711 4489-0 Fax +49 711 4489-118 info@novotechnik.de www.novotechnik.de



© Sep 28, 2021

The specifications contained in our datasheets are intended solely for informational purposes. The documented specification values are based on ideal operational and environmental conditions and can vary significantly depending on the actual customer application. Using our products at or close to one or more of the specified performance ranges can lead to limitations regarding other performance parameters. It is therefore necessary that the end user verifies relevant performance parameters in the intended application. We reserve the right to change product specifications without notice.